

Cera Liquida VX-SL

Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 1/14

Replaced revision:7 (Dated: 04/04/2018)

Safety Data Sheet
According to Annex II to REACH - Regulation 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

Code: 004AVX - 004AVX01 - 004AVX01A - 004AVX005 - 004AVX005A - 004AVX20 - 004AVX200

- 004AVX296 - 004AVX30 Cera Liquida VX-SL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Liquid silicone based product for polishing marble and granite surfaces

1.3. Details of the supplier of the safety data sheet

Name BELLINZONI S.R.L.
Full address Via Mezzano 64
District and Country 28069 Trecate (NO)

Italia

Tel. +39 0321 770558 - +39 02 33912133

Fax +39 02-33915224

e-mail address of the competent person

responsible for the Safety Data Sheet | laboratorio@bellinzoni.com

Product distribution by: BELLINZONI S.r.I.

1.4. Emergency telephone number

For urgent inquiries refer to E.U.: Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. +39 0266101029

### **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Carcinogenicity, category 2 H351 Suspected of causing cancer. Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation.

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

Hazardous to the aquatic environment, chronic toxicity, H411 Toxic to aquatic life with long lasting effects.

category 2

#### 2.2. Label elements



Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 2/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

#### Hazard pictograms:







Signal words: Warning

#### Hazard statements:

H351 Suspected of causing cancer.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

**H317** May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH210 Safety data sheet available on request.

#### Precautionary statements:

P201 Obtain special instructions before use.

**P202** Do not handle until all safety precautions have been read and understood.

P312 Call a POISON CENTRE / doctor / . . . if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

**P280** Wear protective gloves/ protective clothing / eye protection / face protection. **P304+P340** IF INHALED: remove person to fresh air and keep comfortable for breathing.

Contains: Tetrachloroethylene

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### **SECTION 3. Composition/information on ingredients**

# 3.2. Mixtures

#### Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Tetrachloroethylene

CAS 127-18-4 85 ≤ x < 100 Carc. 2 H351, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, STOT

SE 3 H336, Aquatic Chronic 2 H411

EC 204-825-9

INDEX 602-028-00-4



Cera Liquida VX-SL

Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 3/14

Replaced revision:7 (Dated: 04/04/2018)

Reg. no. 01-2119475329-28

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures



Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 4/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s)

Information not available

### **SECTION 8. Exposure controls/personal protection**

# 8.1. Control parameters

### Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018- 0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos



România

ROU

# **BELLINZONI S.R.L.**

Revision nr. 8

Dated 29/01/2020 Printed on 23/03/2020

Page n. 5/14

Replaced revision:7 (Dated: 04/04/2018)

138 mg/m3

39.4 mg/kg

bw/d

# Cera Liquida VX-SL

trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018 HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
Hygieniska gränsvärden, AFS 2018:1
Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

SWE EU Sverige OEL EU

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2019

Туре	Country	TWA/8h	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	138	20	275	40	SKIN			
TLV	CZE	138	20,286	275	40,425	SKIN			
AGW	DEU	69	10	138	20	SKIN			
TLV	DNK	70	10			SKIN			
VLA	ESP	138	20	275	40	SKIN			
VLEP	FRA	138	20	275	40				
WEL	GBR	138	20	275	40	SKIN			
TLV	GRC	138	20	275	40	SKIN			
VLEP	ITA	138	20	275	40	SKIN			
TGG	NLD	138		275		SKIN			
NDS/NDSCh	POL	85		170		SKIN			
VLE	PRT	138	20	275	40	SKIN			
TLV	ROU	50	7	100	14	SKIN			
NGV/KGV	SWE	70	10	170	25	SKIN			
OEL	EU	138	20	275	40	SKIN			
TLV-ACGIH		170	25	678	100				
Predicted no-effect concen-	tration - PNEC								
Normal value in fresh water			0,05	mg/					
Normal value in marine water			0,005	mg/	l				
Normal value for fresh water sediment				0,9	mg/	kg			
Normal value for marine water sediment				0,009	mg/	kg			
Normal value for water, intermittent release				3	mg/	I			
Normal value of STP microorganisms				11,2	mg/	I			
Normal value for the terrestrial compartment				0,01	mg/	kg			
Health - Derived no-effect level - DNEL / DMEL  Effects on consumers				Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral				1.3 mg/kg					

bw/d

bw/d

34.5 mg/m3

23 mg/kg

275

275 mg/m3

138 mg/m3

# Legend:

Skin

Inhalation



Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 6/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 170 mg/m3

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

# ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### **SECTION 9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance liquid



Revision nr. 8

Dated 29/01/2020
Printed on 23/03/2020

Page n. 7/14

Replaced revision:7 (Dated: 04/04/2018)

Cera Liquida VX-SL

Colour opalescent

Odour characteristic of solvent

Odour threshold Not available Not available рН Not available Melting point / freezing point Initial boiling point 121 °C Boiling range Not available 121 °C Flash point **Evaporation Rate** Not available Flammability of solids and gases Not available Not available Lower inflammability limit Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available

> Not available Not available

Relative density 1,48

Solubility insoluble in water

Partition coefficient: n-octanol/water Not available

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity Not available

Explosive properties Not available

Oxidising properties Not available

9.2. Other information

Vapour pressure

Vapour density

VOC (Directive 2010/75/EC): 96,00 %

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Tetrachloroethylene

Decomposes at temperatures above 150°C/302°F.Decomposes if exposed to: UV rays,moisture.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions



Revision nr. 8

Dated 29/01/2020
Printed on 23/03/2020

Page n. 8/14

Replaced revision:7 (Dated: 04/04/2018)

Cera Liquida VX-SL

No hazardous reactions are foreseeable in normal conditions of use and storage.

Tetrachloroethylene

Risk of explosion on contact with: alkaline metals,aluminium,alkaline hydroxides,sodium amides. May react violently with: strong bases, strong oxidising agents, alkaline earth metals, light metals, metal powders, zinc oxide.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Tetrachloroethylene

May develop: hydrogen chloride,phosgenes,chlorine,ethane tetrachloride,chlorine compounds.

# **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Tetrachloroethylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of envoronmental air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Tetrachloroethylene

Has a toxic effect on the central and peripheral nervous system, liver, kidneys and heart; the mucous membranes and the skin are irritated.

Interactive effects

Information not available

### **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: Not classified (no significant component)



Revision nr. 8

Dated 29/01/2020 Printed on 23/03/2020

Page n. 9/14

Replaced revision:7 (Dated: 04/04/2018)

Cera Liquida VX-SL

LD50 (Dermal) of the mixture:
Not classified (no significant component)

Tetrachloroethylene

LD50 (Oral) 3005 mg/kg dw Ratto femmina - OCSE 401

LD50 (Dermal) > 1000 ml/Kg bw coniglio

LC50 (Inhalation) > 3786 mg/l/4h Ratto - OCSE 403

#### SKIN CORROSION / IRRITATION

Causes skin irritation

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Suspected of causing cancer

Tetrachloroethylene

Classified in Group 2A (probable human carcinogen) by the International Agency for Research on Cancer (IARC). Epidemiological studies show evidence of association between exposure to the substance and presence of various types of cancers: bladder cancer, non-Hodgkin's lymphomas and multiple myeloma (US EPA, 2014). Classified as a "probable carcinogen" by the US National Toxicology Program (NTP).

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### **ASPIRATION HAZARD**



Revision nr. 8

Dated 29/01/2020 Printed on 23/03/2020

Page n. 10/14

Replaced revision:7 (Dated: 04/04/2018)

Cera Liquida VX-SL

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. 12.1. Toxicity

Tetrachloroethylene

LC50 - for Fish 5 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 8,5 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

3,64 mg/l/72h Chlamydomonas reinhardtii

Chronic NOEC for Fish

1,99 mg/l 10 giorni Jordanella floridae

Chronic NOEC for Crustacea

510 mg/l 28 giorni Daphnia magna

#### 12.2. Persistence and degradability

Tetrachloroethylene

Solubility in water 150 mg/l

Degradability: information not available

#### 12.3. Bioaccumulative potential

Tetrachloroethylene

Partition coefficient: n-octanol/water 2,53

12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be



Revision nr. 8

Dated 29/01/2020 Printed on 23/03/2020

Page n. 11/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

#### 14.1. UN number

ADR / RID, IMDG,

1897

IATA:

### 14.2. UN proper shipping name

ADR / RID: TETRACHLOROETHYLENE SOLUTION IMDG: TETRACHLOROETHYLENE SOLUTION IATA: TETRACHLOROETHYLENE SOLUTION

#### 14.3. Transport hazard class(es)

ADR / RID:

Class: 6.1

Label: 6.1

IMDG:

Class: 6.1

Label: 6.1

IATA:

Class: 6.1

Label: 6.1



#### 14.4. Packing group

ADR / RID, IMDG, IATA:

Ш

#### 14.5. Environmental hazards

ADR / RID:

Environmentally

Hazardous

IMDG:

Marine Pollutant

IATA:

NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

#### 14.6. Special precautions for user

ADR / RID:

HIN - Kemler: 60

Limited Quantities: 5 Tunnel restriction code: (E)

Special Provision: -



Cera Liquida VX-SL

Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 12/14

Replaced revision:7 (Dated: 04/04/2018)

Quantities: 5

quantity: 60 L

Limited

Maximum quantity: 220

ntity: 220 instructions: 663

Maximum

Packaging instructions:

Packaging

655

Special Instructions:

EMS: F-A, S-A

Cargo:

Pass.:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

IMDG:

IATA:

# **SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



Revision nr. 8

Dated 29/01/2020

Printed on 23/03/2020

Page n. 13/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2 Carcinogenicity, category 2

Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2 Skin irritation, category 2

Skin Sens. 1 Skin sensitization, category 1

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H351 Suspected of causing cancer.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH210 Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY



Revision nr. 8

Dated 29/01/2020 Printed on 23/03/2020

Page n 14/14

Replaced revision:7 (Dated: 04/04/2018)

# Cera Liquida VX-SL

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 11 / 16.